

SECRET

PROJECT
"TOWN HALL"
AIR LAUNCHED
PHOTO RECONNAISSANCE
SATELLITE

NRO REVIEW COMPLETED

USAF review(s) completed.

A7 1011
26 JUN 62

SECRET

SECRET

SECRET

ORIGINAL PROPOSAL


Concept

AIR LAUNCH FOR:

- QUICK REACTION
- LAUNCH AND RECOVERY FLEXIBILITY
- SECURE OPERATIONS
- INCREASED PAYLOAD CAPABILITY
- OMNI-DIRECTIONAL TARGET APPROACH

SINGLE PASS SYSTEM FOR:


- SIMPLICITY
- INVULNERABILITY



Growth Capability to Multiple Pass Operation

Configuration

WAC "MINUTEMAN" BOOSTER: GROSS WT. 52,600 LBS.
(1ST STAGE SHORTENED 81") PAYLOAD CAPABILITY 1115 LBS.



GROUND

SECRET

AS 1915
CS 0062

SECRET

SECRET

SUBSEQUENT STUDIES

MISSILE DESIGN

- INCREASED PAYLOAD BY INCREASED BOOSTER SIZE (MINUTEMAN AND NEW BOOSTERS)
- EVALUATION OF ENVIRONMENTAL EFFECTS ON MOTORS

AIRPLANE STUDIES

- DETERMINE MAX. BOOSTER SIZE COMPATIBLE WITH B-58
- WIND TUNNEL TEST PROGRAM & A/P PERFORMANCE STUDY

PERFORMANCE

- OPTIMUM COMBINATION OF MISSILE/B-58 PERFORMANCE
- COMPARISON OF GROUND AND AIR LAUNCHING

PAYLOAD

- ADVANCED GUIDANCE AND CONTROL CONCEPTS
- MULTIPLE PASS REQUIREMENTS AND CAPABILITIES

GINNIIID

SECRET

40 1012
28 JUN 62


SECRET

SUMMARY OF STUDY RESULTS

ACCELERATION LIMITS:

J79-5B ENGINES
(PRESENT B-58)

IMPROVED
J79 ENGINES



10 0029A
20 JUNE 62

SECRET

SECRET


INTEGRATED GUIDANCE & CONTROL SYSTEM

(Based on system under development by United Aircraft)

SYSTEM COMPONENTS

- HIGH QUALITY INERTIAL PLATFORM
- WIDE ANGLE STAR MONITOR
- MEGACYCLE DIGITAL COMPUTER
- HYPERGOLIC VERNIER PROPULSION
- COLD GAS ATTITUDE CONTROL

SYSTEM OPERATION



AD 1022
27 JUN 62

SECRET





SECRET

SECRET

INTEGRATED VS. CONVENTIONAL SYSTEM COMPARISON

PERFORMANCE FEATURES

MULTIPLE PASS MISSION (8 passes, no tracking)

	CONVENTIONAL PURE INERTIAL SYSTEM	INTEGRATED STELLAR INERTIAL G-CP SKS.
ON-ORBIT POSITION ACCURACY		
DE-ORBIT RECOVERY ACCURACY		

OPERATIONAL FEATURES

FOR INTEGRATED SYSTEM

- Launch w/o accurate Pos. & Az.
- Orbit changes possible during mission
- Thrust-termination not critical
- Vernier recovery guidance possible

AVAILABILITY

- Conventional system — 9 months
- Integrated system — 18 months

RECOMMENDED APPROACH

- Interim conventional system
- Grow into fully integrated system

SECRET


SECRET

SYSTEM POTENTIAL

B-58



+




MINUTEMAN

=

MOBILE (INEXPENSIVE)
LAUNCH CAPABILITY

SATELLITE
INTERCEPT
CAPABILITY



COVERT PHOTO
RECONNAISSANCE
CAPABILITY



OTHER APPLICATIONS

- EQUATORIAL SATELLITES
- ADVANCED ICBM POTENTIAL
- MOBILE SPACE PROBES

AD 1018
26 JUN 62

SECRET




SECRET

SATELLITE INTERCEPTOR SYSTEM ADD-40

REQUIREMENTS

- EARLY CAPABILITY
- DIRECT INTERCEPT
- COLD WAR SYSTEM
- COVERT CAPABILITY
- NUCLEAR or NON-NUCLEAR KILL
- EXISTING BOOSTERS
- 800-1000 N.M. CAPABILITY
- COMPATIBLE WITH SPADATS

LAUNCH TECHNIQUES



AD 10115
26 JUN 62

SECRET

SECRET

SECRET

COMPARISON OF LAUNCH TECHNIQUES

APPROACH


ANALYSIS OF:

- SPADATS CAPABILITY/ACCURACY
 - EFFECT OF TERMINAL GEOMETRY ON MISS DISTANCE
 - ERROR CORRECTION CAPABILITY
 - WARHEAD DEPLOYMENT ERRORS
- TO DETERMINE:
- INTERCEPT GEOMETRY FOR MAXIMUM EFFECTIVENESS
 - INFLUENCE OF ERRORS

RESULTS


SURFACE LAUNCH

EPHEMERIS TIME ERROR MOST IMPORTANT



AIR LAUNCH


EPHEMERIS CROSSTRACK POSITION MOST IMPORTANT



SECRET

SECRET

COMPARISON OF TOWN HALL & SATELLITE INTERCEPTOR




GROUP

SECRET

AD 1019
26 JUN 62

SECRET

BOOSTER CAPABILITIES




GROUP

SECRET

AD 0391
5 JUN 62

SECRET

BOOSTER/AIRPLANE CAPABILITIES




SECRET

SECRET

SYSTEM OPERATION

SECRET

PRE-FLIGHT




- AIRCRAFT PREPARED FOR FLIGHT
- MISSILE GUIDANCE ALIGNED AND TRIMMED
- INITIAL EPHEMERIS AND TRAJECTORY LOADED
- SYSTEM CHECK-OUT

COMPOSITE FLIGHT



- AIRCRAFT FLOWN TO PRE-COMPUTED COURSE
- MISSILE GUIDANCE NAVIGATES AIRCRAFT
- UPDATED EPHEMERIS ENTERED

BOOST



- LAUNCH POINT DETERMINED BY GUIDANCE COMPUTER
- BOOSTER BURNS OUT WITH VELOCITY IN ORBIT PLANE
- INTERCEPTOR SEPARATES FROM BOOSTER

TERMINAL PHASE

- INTERCEPTOR SEARCHES EXPECTED AREA
- TARGET ACQUIRED AT -50-80 N.M.I.
- LOS, RELATIVE BEARING + ANGULAR RATE ESTABLISHED

- INTERCEPTOR YAWED 90° FROM LOS
- ENGINE IGNITED TO THRUST TOWARD ORBIT

- WHEN LOS RATE IS ZERO VEHICLE YAWED TO THRUST ALONG LOS ON COLLISION COURSE
- WARHEAD DEPLOYED ON RANGE-TO-TARGET BASIS

GUIDED


SECRET

AL 0939A
1 JAN 62

SECRET

SECRET

ADO-40/TOWN HALL RELATIONSHIP



SECRET

FORM 10-1136
6 AUG 62

SECRET

CONCLUSIONS AND RECOMMENDATIONS

- ADO-40 system and various covert recon. systems are being studied and evaluated by separate contractor and USAF groups.
- This dual separate approach may well result in choice of two systems, optimum for each mission, but entirely different in hardware items.
- The mobile launch concept is competitive for each mission and should be evaluated simultaneously by USAF personnel cognizant of both missions.
- Choice of mobile launch concept could lead to greatly reduced development costs, operational costs and reliability improvements through adoption of a standard boost vehicle for dual purpose use.

FORM 1
A D 1129
2 NOV 62

SECRET